| COMMUNICATIONS RESOURCE AVAILABILITY WORKSHEET | | | | | | | | Frequency Band: Ham Radio UHF, VHF, HF | Description: Thunderbird and Whale 2022 |
|---|---|---|---|---|---|---|---|---|---|
| Pg No | Channel Configuration | Channel Name/Trunked Radio System Talkgroup | Eligible Users | RX Freq N or W | RX Tone/NAC | TX Freq N or W | Tx Tone/NAC | Mode A, D or M | Remarks |
| | HF | 80 Meters | Amatuer | 3.9850 | none | 3.9850 | none | A | Primary, monitor top of hour |
| | HF | 80 Meters | Amatuer | 3.9900 | none | 3.9900 | none | A | Secondary, top of the hour |
| | HF | 40 Meters | Amatuer | 7.2450 | none | 7.2450 | none | A | Primary, Bottom of the hour |
| | HF | 40 Meters | Amatuer | 7.2500 | none | 7.2500 | none | A | Secondary, Bottom of the hour |
| | HF | 20 Meters | Amatuer | 14.2350 | none | 14.2350 | none | A | Primary |
| | HF | 20 Meters | Amatuer | 14.2400 | none | 14.2400 | none | A | Secondary |
| | | | | | | | | | |
| | VHF Repeater | Tiger Mt | Amatuer | 146.8200 | 103.5 | 146.2200 | 103.5 | A | Covers South Puget Sound |
| | VHF Repeater | Everett | Amatuer | 147.1800 | 103.5 | 147.7800 | 103.5 | A | Snohomish County |
| | VHF Repeater | SnoCo DEM | Amatuer | 146.9200 | 123.0 | 146.3200 | 123.0 | A | Snohomish County DEM |
| | | | | | | | | | |
| | VHF Simplex | Local Tac | Amatuer | 146.5500 | none | 146.5500 | none | A | Tactical |
| | VHF Simplex | Local Tac | Amatuer | 146.4900 | none | 146.4900 | none | A | Tactical |
| | | | | | | | | | |
| | Winlink | | Amatuer | | | | | D | NTEMC@winlink.org |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |

**The convention calls for frequency lists to show four digits after the decimal place, followed by either an “N” or a “W”, depending on whether the frequency is narrow or wide band. Mode refers to either “A” or “D” indicating analog or digital (e.g. Project 25) or "M" indicating mixed mode. All channels are shown as if programmed in a control station, mobile or portable radio. Repeater and base stations must be programmed with the Rx and Tx reversed.**